

11204G15 SNR 20x47x40mm Width 40mm Self aligning ball bearings

| | |
|---|------------|
| d1 | 29.2 mm |
| D1 | 38.6 mm |
| rs min | 1 mm |
| e | 0.28 |
| Y1 | 2.24 |
| Y2 | 3.46 |
| Y0 | 2.35 |
| Radial clearance class | CN |
| Precision class | P0 |
| Mass | 0.19 kg |
| Dynamic load, C | 9.9 kN |
| Static load, C0 | 2.6 kN |
| Nref | 15.000 rpm |
| Nlim | 18.000 rpm |
| Min operating temperature, Tmin | -20 °C |
| Max operating temperature, Tmax | 120 °C |
| Characteristic cage frequency, FTF | 0.41 Hz |
| Characteristic rolling element frequency, BSF | 5.02 Hz |
| Characteristic outer ring frequency, BPF0 | 4.87 Hz |
| Characteristic inner ring frequency, BRFI | 7.13 Hz |
| da min | 25 mm |
| Da max | 42 mm |
| ra max | 1 mm |
| Bearing number | 11204G15 |

| | |
|---------------------|-----------|
| Size (mm) | 20x47x40 |
| Brand | SNR |
| Bore Diameter (mm) | 20.000 |
| Outer Diameter (mm) | 47.000 |
| Width (mm) | 40 |
| d | 20.000 mm |
| D | 47.000 mm |
| B | 40 mm |
| C | 14 mm |