

1213 SNR B 23.000 mm 65x120x23mm Self aligning ball bearings

| | |
|-----------------------------------------------|-----------|
| d1 | 85.5 mm |
| D1 | 102.7 mm |
| rs min | 1.5 mm |
| e | 0.17 |
| Y1 | 3.7 |
| Y2 | 5.73 |
| Y0 | 3.88 |
| Radial clearance class | CN |
| Precision class | P0 |
| Mass | 1.13 kg |
| Dynamic load, C | 30.7 kN |
| Static load, C0 | 12.5 kN |
| Nref | 5.900 rpm |
| Nlim | 7.300 rpm |
| Min operating temperature, Tmin | -40 °C |
| Max operating temperature, Tmax | 120 °C |
| Characteristic cage frequency, FTF | 0.44 Hz |
| Characteristic rolling element frequency, BSF | 8.3 Hz |
| Characteristic outer ring frequency, BPF0 | 9.26 Hz |
| Characteristic inner ring frequency, BRFI | 11.74 Hz |
| da min | 73 mm |
| Da max | 112 mm |
| ra max | 1.5 mm |
| Bearing number | 1213 |

| | |
|---------------------|------------|
| Size (mm) | 65x120x23 |
| Brand | SNR |
| Bore Diameter (mm) | 65.000 |
| Outer Diameter (mm) | 120.000 |
| Width (mm) | 23.000 |
| d | 65.000 mm |
| D | 120.000 mm |
| B | 23.000 mm |
| C | 23.000 mm |