

1215K KOYO (Grease) Lubrication Speed 4300 r/min 75x130x25mm Self aligning ball bearings

Bearing number	1215K
Size (mm)	75x130x25
Brand	KOYO
Bore Diameter (mm)	75
Outer Diameter (mm)	130
Width (mm)	25
d	75 mm
D	130 mm
B	25 mm
C	25 mm
r min.	1.5 mm
da min.	83 mm
Da max.	122 mm
ra max.	1.5 mm
Weight	1.34 Kg
Basic dynamic load rating (C)	38.8 kN
Basic static load rating (C0)	15.7 kN
(Grease) Lubrication Speed	4300 r/min
(Oil) Lubrication Speed	5300 r/min
Calculation factor (e)	0.17

Calculation factor (Y0)	3.77
Calculation factor (Y1)	3.60
Category	Self Aligning Ball Bearings
BDI Inventory	0.0
Manufacturer Name	KOYO
Minimum Buy Quantity	N/A
Weight / Kilogram	0
EAN	0605790369728
Product Group – BDI	B00152
Mounting Method	Tapered Adapter
Enclosure	Open
Rolling Element	Ball Bearing
Adapter Sleeve	H-215X
Cage Material	Steel
Precision Class	ABEC 1 ISO P0
Internal Clearance	C0-Medium
Number of Rows of Balls	Double Row
Other Features	Allowable Misalignment 2.5 Deg 1:12 Taper
Long Description	75MM Bore; Tapered Adapter Mount; 130MM Outside Diameter; 25MM Inner Race Width; 25MM Outer Race Width; Open; Steel Cage; Double Row of Balls; ABEC 1 ISO P0; C0-Medium
Inch – Metric	Metric
Category – BDI	Self Aligning Ball Bearings
UNSPSC	31171532
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Self Aligning

Manufacturer URL	http://www.koyousa.com
Weight / LBS	2.95419
Outside Diameter	5.118 Inch 130 Millimeter
Outer Race Width	0.984 Inch 25 Millimeter
Bore	2.953 Inch 75 Millimeter
Inner Race Width	0.984 Inch 25 Millimeter