

1307K NACHI 35x80x21mm Adapter Sleeve H-307X Self aligning ball bearings

| | |
|----------------------------------|------------|
| Bearing number | 1307K |
| Size (mm) | 35x80x21 |
| Brand | NACHI |
| Bore Diameter (mm) | 35 |
| Outer Diameter (mm) | 80 |
| Width (mm) | 21 |
| d | 35 mm |
| D | 80 mm |
| B | 21 mm |
| C | 21 mm |
| r1 min. | 1.5 mm |
| da min. | 43 mm |
| Da max. | 72 mm |
| ra max. | 1.5 mm |
| Weight | 0.510 Kg |
| Basic dynamic load rating (C) | 25.1 kN |
| Basic static load rating (C0) | 7.85 kN |
| (Grease) Lubrication Speed | 7900 r/min |
| (Oil) Lubrication Speed | 9700 r/min |
| Calculation factor (e) | 0.25 |
| Calculation factor (Y0) | 2.60 |
| Calculation factor (Y1) | 2.48 |

| | |
|-------------------------|--|
| Category | Self Aligning Ball Bearings |
| BDI Inventory | 0.0 |
| Manufacturer Name | NACHI |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0 |
| Product Group – BDI | B00152 |
| Mounting Method | Tapered Adapter |
| Enclosure | Open |
| Rolling Element | Ball Bearing |
| Adapter Sleeve | H-307X |
| Cage Material | Steel |
| Precision Class | ABEC 1 ISO P0 |
| Internal Clearance | C0-Medium |
| Number of Rows of Balls | Double Row |
| Other Features | Allowable Misalignment 3 Deg 1:12 Taper |
| Long Description | 35MM Bore; Tapered Adapter Mount; 80MM Outside Diameter; 21MM Inner Race Width; 21MM Outer Race Width; Open; Steel Cage; Double Row of Balls; ABEC 1 ISO P0; C0-Medium |
| Inch – Metric | Metric |
| Category – BDI | Self Aligning Ball Bearings |
| UNSPSC | 31171532 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Self Aligning |
| Manufacturer URL | http://www.nachi.com |
| Weight / LBS | 1.12436 |
| Bore | 1.378 Inch 35 Millimeter |

| | |
|------------------|----------------------------|
| Outer Race Width | 0.827 Inch 21 Millimeter |
| Outside Diameter | 3.15 Inch 80 Millimeter |
| Inner Race Width | 0.827 Inch 21 Millimeter |