

# 15580/15523

# NSK

## 26.988×60.325×19.842mm inner

## ra 3.5 Tapered roller

## bearings

Bearing number	15580/15523
Size (mm)	26.988×60.325×19.842
Brand	NSK
Bore Diameter (mm)	26.988
Outer Diameter (mm)	60.325
Width (mm)	19.842
d	26.988 mm
D	60.325 mm
T	19.842 mm
B	17.462 mm
C	15.875 mm
ra1 max.	1.5 mm
a	14.7 mm
r min.	3.5 mm
r1 min.	1.5 mm
Da	51 mm
db	32 mm
ra max.	3.5 mm
da	38.5 mm
Db	54 mm
Weight	0.264 Kg
Basic dynamic load rating (C)	39.5 kN

Basic static load rating (C0)	45.5 kN
(Grease) Lubrication Speed	6700 r/min
(Oil) Lubrication Speed	9000 r/min
Calculation factor (e)	0.35
Calculation factor (Y0)	0.95
LangID	1
ALP23	0
outer r	1.5
ALP22	0
D_	60.325
ALP21	26
SHOG_yobi	15580R/15523R
RAr	115.199
inner r	3.5
GRS rpm	6700
D_b	54
D_a	51
DE_	49.013
SLR	12.2
Prod_Type3	TRBSR_ID_A
BETA_	1
ALPHA_	13
SDM_	42.568
calcUrl	/BearingGuide/html/calculation.jsp
DA1	7.036
DA2	6.294
hidYobi	15580/15523
Y1	1.7

B_	17.462
Oil rpm	9000
hidTable	ecat_NSTPRI
Y0	0.95
inner ra	3.5
outer rb	1.5
C0	45.5
CUP	0.123
e	0.35
DA_	6.667
BET21	3
BET22	30
BET23	0
Z_	17
C_	15.875
yobi	15580/15523
KBRG	3161
CONE	0.141
DI_	35.977