

# 16026 NSK 130x200x22mm SBRG 0 Deep groove ball bearings

Bearing number	16026
Size (mm)	130x200x22
Brand	NSK
Bore Diameter (mm)	130
Outer Diameter (mm)	200
Width (mm)	22
d	130 mm
D	200 mm
B	22 mm
C	22 mm
r min.	1.1 mm
da min.	136.5 mm
Da max.	193.5 mm
fa max.	1 mm
Weight	2.4 kg
Basic dynamic load rating (C)	75.5 kN
Basic static load rating (C0)	77.5 kN
(Grease) Lubrication Speed	3 000 r/min
(Oil) Lubrication Speed	3 000 r/min
Category	Single Row Ball Bearings
BDI Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	2.7
SKN	0029176031304
Product Group - BDI	809388
Enclosure	Open
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	130MM Bore; 200MM Outside Diameter; 22MM Outer Race Diameter; Open; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category - BDI	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.59.60
Noun	Bearing
Keyword String	Ball
Manufacturer URL	<a href="http://www.nskamericas.com">http://www.nskamericas.com</a>
Weight / LBS	5.952
Bore	5.118 Inch   130 Millimeter
Outside Diameter	7.874 Inch   200 Millimeter
Outer Race Width	0.866 Inch   22 Millimeter
bore diameter:	130 mm
closure type:	Open
outside diameter:	200 mm
internal clearance:	Normal Clearance
overall width:	22 mm
manufacturer upc number:	029176031304
bore type:	Round
SKN	8.63
NSK P/N	16026
length	1
D	200
SREX	0.83
B	22
CAD	<a href="https://service.webcad.co.jp/pcon/maker_login.php?maker=NSK_R&amp;language=j&amp;info=nsk_rb/roller_bearings/deep_groove_bb/single_row_dgbb/open_type_asmtab.prj&amp;varset(STA=...)_(ORDER=16026)_(SD=130)_(D=200)_(B=22)_(E=1.1)_(CR1=75500)_(COR1=77500)_(FO=16.4)_(LG=3000)_(LD=3600)_(DM1=136.5)_(DA1=0.8)_(DA2=193.5)_(RA=1.0)_(PM55=2.400)">https://service.webcad.co.jp/pcon/maker_login.php?maker=NSK_R&amp;language=j&amp;info=nsk_rb/roller_bearings/deep_groove_bb/single_row_dgbb/open_type_asmtab.prj&amp;varset(STA=...)_(ORDER=16026)_(SD=130)_(D=200)_(B=22)_(E=1.1)_(CR1=75500)_(COR1=77500)_(FO=16.4)_(LG=3000)_(LD=3600)_(DM1=136.5)_(DA1=0.8)_(DA2=193.5)_(RA=1.0)_(PM55=2.400)</a>
da min	136.5
nsftable	ecat_85000
d11 rpm	3600
SRE	0.63
bas5	2.4
OSI rpm	3600
ra	1
SREX	0.83
D_a	193.5
SREN	-0.03
CS	77.5
fo	16.4
SREN	-0.03
DE	181.609
Prod_type3	0008_00_07
DA	16.609
bomp	0
Z	17
y001	16026
C_code	75500
ALPHA	0
SDM	165
r	1.1
NSK	6103
SBRG	0
D1	148.331
calcdirt	/bearingGuide/html/calculation.jsp