

# 16032 NSK 160x240x25mm bomp 0 Deep groove ball bearings

Bearing number	16032
Size (mm)	160x240x25
Brand	NSK
Bore Diameter (mm)	160
Outer Diameter (mm)	240
Width (mm)	25
d	160 mm
D	240 mm
B	25 mm
C	23 mm
r min.	1.5 mm
da min.	168 mm
Da max.	232 mm
ra max.	1.5 mm
Weight	4.2 kg
Basic dynamic load rating (C)	99 kN
Basic static load rating (C0)	188 kN
(Grease) Lubrication Speed	2 400 r/min
(Oil) Lubrication Speed	2 000 r/min
SRI	9.86
ISO001	16032
ISO02	1
SRIK	0.64
B	25
CAD	<a href="https://service.web3cad.co.jp/pctm/maker_login.php?Maker=NSK_R&amp;language=ja&amp;info=ok_rb/roller_bearings/deep_groove_bb/single_row_dgb/open_type_sontab.prj&amp;varset={STAN=3,(MODE=16032),(SD=160),(D=240),(B=25),(CR1=99900),(COR1=100000),(FO=16.5),(LG=2400),(LO=2000),(DMP1=160.0),(DA1=0.0),(DA2=232.0),(PA=1.5),(PKS5=4.200)}">https://service.web3cad.co.jp/pctm/maker_login.php?Maker=NSK_R&amp;language=ja&amp;info=ok_rb/roller_bearings/deep_groove_bb/single_row_dgb/open_type_sontab.prj&amp;varset={STAN=3,(MODE=16032),(SD=160),(D=240),(B=25),(CR1=99900),(COR1=100000),(FO=16.5),(LG=2400),(LO=2000),(DMP1=160.0),(DA1=0.0),(DA2=232.0),(PA=1.5),(PKS5=4.200)}</a>
hidTable	ecat_NSR0GB
Oil rpm	2800
SRI	9.86
SRIK	4.2
GRS rpm	2400
ra	1.5
SRIK	0.64
D_a	232
SRIK	-0.64
C0	188
fo	16.5
SRIK	-0.64
DE	230.05
Prod_Type3	DGBB_SR_0T
da_	168.05
bomp	0
Z	18
yob1	16032
C_conv	99000
ALPHA_	0
SDK_	200
r	1.5
KBRG	0194
SBRG	0
DI	180.95
calcort	/BearingGuide/html/calculation.jsp