

1726211-2RS1 SKF 100x55x21mm

Basic dynamic load rating C

43.6 kN Deep groove ball bearings

Bearing number	1726211-2RS1
Size (mm)	100x55x21
Brand	SKF
Bore Diameter (mm)	100
Outer Diameter (mm)	55
Width (mm)	21
d	55 mm
D	100 mm
B	21 mm
d ₁	69.06 mm
r _{1,2} – min.	1.5 mm
Basic dynamic load rating – C	43.6 kN
Basic static load rating – C ₀	29 kN
Fatigue load limit – P _u	1.2 kN
Limiting speed	4300 r/min
Calculation factor – f ₀	14
Category	Insert Bearings Spherical OD
BDI Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.54
EAN	7316570115581

Product Group – BDI	M06110
Inner Race Profile	Standard Inner Ring
Outer Race Profile	Spherical
Relubricatable	No
Seal Type	RS1 Seal
Mounting Method	Shaft Mount
Rolling Element	Ball Bearing
Snap Ring	No
Long Description	55MM Bore; Standard Inner Ring; Ball Bearing; 21MM Length Thru Bore; 21MM Outer Race Width; 100MM Outside Diameter; Not Relubricatable; RS1 Seal Seal; Shaft Mount Mounting Method; No Snap Ring
Inch – Metric	Metric
Other Features	Single Row Standard Duty Metric
Category – BDI	Insert Bearings
UNSPSC	31171536
Harmonized Tariff Code	8482.10.50.00
Noun	Bearing
Keyword String	Insert
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	1726211-2RS1
Weight / LBS	1.19
Outer Race Width	0.827 Inch 21 Millimeter
Bore	2.165 Inch 55 Millimeter
Outside Diameter	3.937 Inch 100 Millimeter
Length Thru Bore	0.827 Inch 21 Millimeter

bore diameter:	55 mm
radial static load capacity:	29 kN
outside diameter:	100 mm
finish/coating:	Uncoated
outer ring width:	21 mm
maximum rpm:	4300 RPM
bore type:	Round
seal type:	Contact/Lip
operating temperature range:	-40 to +210 °F
series:	17262
radial dynamic load capacity:	43.6 kN
$d_1 \approx$	69.06 mm
$r_{1,2} \text{ min.}$	1.5 mm
Basic dynamic load rating C	43.6 kN
Basic static load rating C_0	29 kN
Fatigue load limit P_u	1.25 kN
Limiting speed ¹⁾	4300 r/min
Calculation factor f_0	14
Mass complete bearing	0.6 kg