

20213-K-TVP-C3 FAG da min 74 mm 65x120x23mm Spherical roller bearings

| | |
|---------------------|--|
| Bearing number | 20213-K-TVP-C3 |
| Size (mm) | 65x120x23 |
| Brand | FAG |
| Bore Diameter (mm) | 65 |
| Outer Diameter (mm) | 120 |
| Width (mm) | 23 |
| d | 65 mm |
| D | 120 mm |
| B | 23 mm |
| D_1 | 105.1 mm |
| $D_{a \max}$ | 111 mm |
| $d_{a \min}$ | 74 mm |
| $r_{a \max}$ | 1.5 mm |
| r_{\min} | 1.5 mm |
| m | 1.07 kg / Weight |
| C_r | 95000 N / Dynamic load rating (radial) |
| C_{0r} | 116000 N / Static load rating (radial) |
| n_G | 6000 1/min / Limiting speed |
| C_{ur} | 12700 N / Fatigue limit load. radial |
| Bearing number | 20213-K-TVP-C3 |

| | |
|----------------------------------|-----------|
| Size (mm) | 65x120x23 |
| Brand | FAG |
| Bore Diameter (mm) | 65 |
| Outer Diameter (mm) | 120 |
| Width (mm) | 23 |
| d | 65 mm |
| D | 120 mm |
| B | 23 mm |
| C | 23 mm |
| r min. | 1.5 mm |
| D1 | 105.1 mm |
| da min. | 74 mm |
| Da max. | 111 mm |
| ra max. | 1.5 mm |
| Weight | 1.07 Kg |
| Basic dynamic load rating (C) | 95 kN |
| Basic static load rating (C0) | 116 kN |
| Fatigue load limit (Pu) | 12.7 |