

209-2Z SKF 85x45x19mm Basic dynamic load rating C 35.2 kN Deep groove ball bearings

Bearing number	209-2Z
Size (mm)	85x45x19
Brand	SKF
Bore Diameter (mm)	85
Outer Diameter (mm)	45
Width (mm)	19
d	45 mm
D	85 mm
B	19 mm
d_1	57.6 mm
D_2	75.19 mm
$r_{1,2} - \text{min.}$	1.1 mm
$d_a - \text{min.}$	52 mm
$d_a - \text{max.}$	57.5 mm
$D_a - \text{max.}$	78 mm
$r_a - \text{max.}$	1 mm
Basic dynamic load rating – C	35.2 kN
Basic static load rating – C_0	30 kN
Fatigue load limit – P_u	1.3 kN
Reference speed	14000 r/min
Limiting speed	6800 r/min
Calculation factor – k_r	0.04

Category	Single Row Ball Bearings
BDI Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.474
EAN	7316577295507
Product Group – BDI	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	Yes
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	45MM Bore; 85MM Outside Diameter; 19MM Outer Race Diameter; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; Yes Filling Slot; No Snap Ring; No Internal Special Features
Category – BDI	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.skf.com

Manufacturer Item Number	209 2Z
Weight / LBS	0.99
Outside Diameter	3.346 Inch 85 Millimeter
Bore	1.772 Inch 45 Millimeter
Outer Race Width	0.748 Inch 19 Millimeter
bore diameter:	45 mm
static load capacity:	30 kN
outside diameter:	85 mm
precision rating:	ABEC 3 (ISO Class 6)
overall width:	19 mm
finish/coating:	Uncoated
bore type:	Round
cage material:	Steel
closure type:	Double Shielded
outer ring width:	19 mm
row type & fill slot:	Single Row Filling Slot
fillet radius:	1 mm
snap ring included:	Without Snap Ring
maximum rpm:	8500 RPM
internal clearance:	C0
series:	20
dynamic load capacity:	35.2 kN
thrust application warning:	This product can not be used in Thrust Applications
$d_1 \approx$	57.6 mm
$D_2 \approx$	75.19 mm
$r_{1,2} \text{ min.}$	1.1 mm
$d_a \text{ min.}$	52 mm
$d_a \text{ max.}$	57.5 mm

D_a max.	78 mm
r_a max.	1 mm
Basic dynamic load rating C	35.2 kN
Basic static load rating C_0	30 kN
Fatigue load limit P_u	1.27 kN
Calculation factor k_r	0.04
Mass bearing	0.44 kg