

2200 NSK 10x30x14mm SRIN 0 Self aligning ball bearings

Bearing number	2200
Size (mm)	10x30x14
Brand	NSK
Bore	
DIauctor (mm)	10
Outer DIauctor (mm)	30
Width (mm)	14
d	10 mm
D	30 mm
B	14 mm
C	14 mm
r min.	0.6 mm
Da min.	14 mm
Da max.	26 mm
ra max.	0.6 mm
Weight	0.042 Kg
Basic dynamic load rating (C)	7.45 kN
Basic static load rating (C0)	1.59 kN
(Grease) Lubrication Speed	24 000 r/min
(Oil) Lubrication Speed	28 000 r/min
Calculation factor (e)	0.64
Calculation factor (YB)	1
Calculation factor (Y2)	1.5
SR	2.92
Y3	0.98
hidfobi	2200
LangID	1
PCD	19.2
D	30
Y2	1.5
SREX	0
cyl count	9
a	14
CAD	http://service.web2cad.co.jp/pcon/?Maker=NSK_NIKinfo=nsk_rb/roller_bearings/self_aligning_ba/cylindrical_bore_sontab.prj&varset={STAB=}, (ORDER=2200), (SD=10), (D=30), (B=14), (R=0.6), (CR1=7450), (CR0=1590), (CR2=760), (CR3=162), (LG=24000), (LO=28000), (DA1=14.0), (DA2=26.0), (RA=0.6), (E=0.64), (Y2=1.5), (Y3=0.98), (YB=1.00), (MSS=0.042)
hidfable	ecat_NSKAB
Oil rpm	28000
SR	0
YB	1
mass	0.042
ra	0.6
GRS rpm	24000
SRZ	0.63
groove inner	13.621
D_2	26
SRZB	0
CB	1.59
groove outer	26.434
SRZB	0
XB	1
Prod_Type3	SABB_SA_CB
X1	1
DB	14
X2	0.65
e	0.64
yobi	2200
F	0.6
K06	1554
CAn	23.127
cyl dia	5.356
calcurl	/bearingGuide/html/calculation.jsp