

2215 SNR Characteristic outer ring frequency, BPF0 8.71 Hz 75x130x31mm Self aligning ball bearings

| | |
|---|-----------|
| d1 | 93.3 mm |
| D1 | 113.8 mm |
| rs min | 1.5 mm |
| e | 0.25 |
| Y1 | 2.5 |
| Y2 | 3.87 |
| Y0 | 2.62 |
| Radial clearance class | CN |
| Precision class | P0 |
| Mass | 1.6 kg |
| Dynamic load, C | 43.8 kN |
| Static load, C0 | 17.8 kN |
| Nref | 5.600 rpm |
| Nlim | 6.300 rpm |
| Min operating temperature, Tmin | -40 °C |
| Max operating temperature, Tmax | 120 °C |
| Characteristic cage frequency, FTF | 0.44 Hz |
| Characteristic rolling element frequency, BSF | 7.51 Hz |
| Characteristic outer ring frequency, BPF0 | 8.71 Hz |
| Characteristic inner ring frequency, BRFI | 11.29 Hz |
| da min | 83 mm |
| Da max | 122 mm |

| | |
|---------------------|------------|
| ra max | 1.5 mm |
| Bearing number | 2215 |
| Size (mm) | 75x130x31 |
| Brand | SNR |
| Bore Diameter (mm) | 75.000 |
| Outer Diameter (mm) | 130.000 |
| Width (mm) | 31.000 |
| d | 75.000 mm |
| D | 130.000 mm |
| B | 31.000 mm |
| C | 31.000 mm |