

22317UAVS2 NTN 85x180x60mm outer ring width: 60 mm Thrust roller bearings

| | |
|---------------------------|---------------------------|
| Bearing number | 22317UAVS2 |
| Size (mm) | 85x180x60 |
| Brand | NTN |
| Bore Diameter (mm) | 85.000 |
| Outer Diameter (mm) | 180.000 |
| Width (mm) | 60.000 |
| d | 85.000 mm |
| D | 180.000 mm |
| H | 60.000 mm |
| Category | Spherical Roller Bearings |
| BDI Inventory | 0.0 |
| Manufacturer Name | NTN |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 7.34 |
| EAN | 4547359270587 |
| Product Group – BDI | B04311 |
| Internal Clearance | C0-Medium |
| Mounting Method | Shaft Mount |
| Rolling Element | Spherical Roller Bearing |
| Bore Profile | Straight |
| Cage Material | Bronze |
| Enclosure | Open |
| Number of Rows of Rollers | Double Row |
| Relubricatable | Yes |

| | |
|------------------------------|---|
| Withdrawal Sleeve | Not Applicable |
| Withdrawal Nut | Not Applicable |
| Inch – Metric | Metric |
| Long Description | 85MM Straight Bore; 180MM Outside Diameter; 60MM Width; C0-Medium Clearance; Shaft Mount; Double Row of Spherical Roller Bearings; Bronze Cage Material; Open Enclosure; Relubricatable |
| Category – BDI | Spherical Roller Bearing |
| UNSPSC | 31171510 |
| Harmonized Tariff Code | 84823080 |
| Noun | Bearing |
| Keyword String | Spherical |
| Manufacturer URL | http://www.ntnamerica.com |
| Weight / LBS | 16.177 |
| Outside Diameter | 7.087 Inch 180 Millimeter |
| Adapter Part Number | Not Applicable Inch Not Applicable Millimeter |
| Bore | 3.346 Inch 85 Millimeter |
| Width | 2.362 Inch 60 Millimeter |
| bore diameter: | 85 mm |
| operating temperature range: | -40 to 120 °C |
| outside diameter: | 180 mm |
| cage material: | Brass |
| overall width: | 60 mm |
| bearing material: | Through Hardened Steel |
| bore type: | Straight |
| cage type: | Machined |

| | |
|----------------------------|----------------------------|
| outer ring type: | Not Split |
| precision rating: | Not Rated |
| internal clearance: | Upper 2/3 of C4 range |
| finish/coating: | Uncoated |
| closure type: | Open |
| outer ring width: | 60 mm |
| lubrication hole type: | Lubrication Groove & Hole |
| inner ring width: | 60 mm |
| dynamic load capacity: | 395000 N |
| fillet radius: | 3 mm |
| static load capacity: | 370000 N |
| series: | 223 |
| maximum rpm: | 2300 rpm |
| manufacturer product page: | Click here |