

22332EMKW33 SNR db min 174 mm 160x340x114mm Thrust roller bearings

B	114 mm
d2	219 mm
D1	295.2 mm
rs min	4 mm
Number of lubrication holes	3
b	20.3 mm
k	10 mm
Associated sleeve reference	H2332
e	0.33
Y1	2.03
Y2	3.02
Y0	1.98
Radial clearance class	CN
Mass	50 kg
Dynamic load, C	1.950 kN
Static load, C0	2.210 kN
Fatigue limit load, Cu	158 kN
Nref	1.400 rpm
Nlim	1.900 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	200 °C
Characteristic cage frequency, FTF	0.41 Hz
Characteristic rolling element frequency, BSF	5.33 Hz
Characteristic outer ring frequency, BPF0	6.58 Hz

Characteristic inner ring frequency, BPFI	9.42 Hz
da min	177 mm
db min	174 mm
Ce min	8 mm
Da max	323 mm
ra max	3 mm
Bearing number	22332EMKW33
Size (mm)	160x340x114
Brand	SNR
Bore Diameter (mm)	160.000
Outer Diameter (mm)	340.000
Width (mm)	114.000
d	160.000 mm
D	340.000 mm
H	114.000 mm