

24034EAK30W33 SNR Da max 249.8 mm 170x260x90mm Thrust roller bearings

B	90 mm
d2	188 mm
D1	232.3 mm
rs min	2.1 mm
Number of lubrication holes	3
b	10.67 mm
k	5 mm
e	0.31
Y1	2.21
Y2	3.29
Y0	2.16
Radial clearance class	CN
Mass	16.6 kg
Dynamic load, C	1.120 kN
Static load, C0	1.580 kN
Fatigue limit load, Cu	97.4 kN
Nref	1.600 rpm
Nlim	2.400 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	200 °C
Characteristic cage frequency, FTF	0.44 Hz
Characteristic rolling element frequency, BSF	8.6 Hz
Characteristic outer ring frequency, BPF0	10.65 Hz
Characteristic inner ring frequency, BRFI	13.35 Hz

da min	180.2 mm
Da max	249.8 mm
ra max	2 mm
Bearing number	24034EAK30W33
Size (mm)	170x260x90
Brand	SNR
Bore Diameter (mm)	170.000
Outer Diameter (mm)	260.000
Width (mm)	90.000
d	170.000 mm
D	260.000 mm
H	90.000 mm