

25TAB06 NACHI Angle (α) 60 ° 25x62x15mm Thrust ball bearings

Bearing number	25TAB06
Size (mm)	25x62x15
Brand	NACHI
Bore Diameter (mm)	25
Outer Diameter (mm)	62
Width (mm)	15
d	25 mm
D	62 mm
B	15 mm
C	15 mm
Angle (α)	60 °
r min.	1 mm
r1 min.	0.6 mm
Weight	0.24 Kg
Basic dynamic load rating (C)	29.9 kN
Basic static load rating (C0)	46.4 kN
(Grease) Lubrication Speed	4650 r/min
Enclosure	Open
Configuration	Single Row
Bore Type	Cylindrical Bore
Bore Size	25 mm
Outside Diameter	62 mm
Width	15 mm
Fillet Radius/Chamfer	1 mm

r1	0.6 mm
a	0 mm
2B	30 mm
Dynamic Load Rating	29.900 N
Static Load Rating	46.400 N
Limiting Speed – Grease	4.650 rpm
Limiting Speed – Oil	6.000 rpm
Starting Torque – Grease Lubrication	20 N·cm
da1 (min)	46.2 mm
da2 (min)	39.7 mm
Da1 (max)	46 mm
Da2 (max)	53.4 mm