

29322EX NACHI 110x190x48mm db1 (max) 116 mm Thrust roller bearings

| | |
|-------------------------------|-----------------|
| Bearing number | 29322EX |
| Size (mm) | 110x190x48 |
| Brand | NACHI |
| Bore Diameter (mm) | 110 |
| Outer Diameter (mm) | 190 |
| Width (mm) | 48 |
| d | 110 mm |
| D | 190 mm |
| T | 48 mm |
| d1 | 165.1 mm |
| r min. | 2 mm |
| A | 64 mm |
| B | 30.9 mm |
| B1 | 44 mm |
| C | 23 mm |
| D1 | 140.6 mm |
| Weight | 5.22 Kg |
| Basic dynamic load rating (C) | 550 kN |
| Basic static load rating (C0) | 1730 kN |
| (Grease) Lubrication Speed | 1300 r/min |
| Category | Roller Bearings |
| BDI Inventory | 0.0 |
| Manufacturer Name | NACHI |
| Minimum Buy Quantity | N/A |

| | |
|-------------------------|------------------|
| Weight / Kilogram | 5.67 |
| Product Group – BDI | B04311 |
| Bore Type | Cylindrical Bore |
| Enclosure | Open |
| Configuration | Single Row |
| Bore Size | 110 mm |
| Outside Diameter | 190 mm |
| Fillet Radius/Chamfer | 2 mm |
| Width | 48 mm |
| Dynamic Load Rating | 550.000 N |
| Static Load Rating | 1.730.000 N |
| Limiting Speed – Grease | 1.300 rpm |
| Limiting Speed – Oil | 2.100 rpm |
| da (min) | 145 mm |
| Da (max) | 165 mm |
| ra (max) | 2 mm |
| db1 (max) | 116 mm |
| db2 (max) | 117 mm |