

# 29340E NACHI Weight / Kilogram 0 200x340x85mm Thrust roller bearings

|                               |            |
|-------------------------------|------------|
| Bearing number                | 29340E     |
| Size (mm)                     | 200x340x85 |
| Brand                         | NACHI      |
| Bore Diameter (mm)            | 200        |
| Outer Diameter (mm)           | 340        |
| Width (mm)                    | 85         |
| d                             | 200 mm     |
| D                             | 340 mm     |
| T                             | 85 mm      |
| d1                            | 325 mm     |
| r min.                        | 4 mm       |
| A                             | 116 mm     |
| B1                            | 29 mm      |
| B2                            | 81 mm      |
| C                             | 41 mm      |
| D1                            | 261 mm     |
| da min.                       | 265 mm     |
| Da max.                       | 295 mm     |
| ra max.                       | 3 mm       |
| Weight                        | 32 Kg      |
| Basic dynamic load rating (C) | 1350 kN    |
| Basic static load rating (C0) | 5250 kN    |
| Category                      | Bearings   |
| BDI Inventory                 | 0.0        |

|                       |                  |
|-----------------------|------------------|
| Manufacturer Name     | NACHI            |
| Minimum Buy Quantity  | N/A              |
| Weight / Kilogram     | 0                |
| Product Group – BDI   | B04311           |
| Bore Type             | Cylindrical Bore |
| Enclosure             | Open             |
| Configuration         | Single Row       |
| Bore Size             | 200 mm           |
| Outside Diameter      | 340 mm           |
| Fillet Radius/Chamfer | 4 mm             |
| Width                 | 85 mm            |
| Dynamic Load Rating   | 1.350.000 N      |
| Static Load Rating    | 5.250.000 N      |
| Limiting Speed – Oil  | 1.000 rpm        |
| B                     | 29 mm            |
| da (min)              | 265 mm           |
| Da (max)              | 295 mm           |
| ra (max)              | 3 mm             |