

# 29412E NACHI 60x130x42mm B2 39.5 mm Thrust roller bearings

|                               |           |
|-------------------------------|-----------|
| Bearing number                | 29412E    |
| Size (mm)                     | 60x130x42 |
| Brand                         | NACHI     |
| Bore Diameter (mm)            | 60        |
| Outer Diameter (mm)           | 130       |
| Width (mm)                    | 42        |
| d                             | 60 mm     |
| D                             | 130 mm    |
| T                             | 42 mm     |
| d1                            | 123 mm    |
| r min.                        | 1.5 mm    |
| A                             | 38 mm     |
| B1                            | 15 mm     |
| B2                            | 39.5 mm   |
| C                             | 20 mm     |
| D1                            | 89 mm     |
| da min.                       | 91 mm     |
| Da max.                       | 108 mm    |
| ra max.                       | 1.5 mm    |
| Weight                        | 2.75 Kg   |
| Basic dynamic load rating (C) | 299 kN    |
| Basic static load rating (C0) | 890 kN    |
| Category                      | Bearings  |
| BDI Inventory                 | 0.0       |

|                       |                  |
|-----------------------|------------------|
| Manufacturer Name     | NACHI            |
| Minimum Buy Quantity  | N/A              |
| Weight / Kilogram     | 0                |
| Product Group – BDI   | B04311           |
| Bore Type             | Cylindrical Bore |
| Enclosure             | Open             |
| Configuration         | Single Row       |
| Bore Size             | 60 mm            |
| Outside Diameter      | 130 mm           |
| Fillet Radius/Chamfer | 1.5 mm           |
| Width                 | 42 mm            |
| Dynamic Load Rating   | 299.000 N        |
| Static Load Rating    | 890.000 N        |
| Limiting Speed – Oil  | 2.800 rpm        |
| B                     | 15 mm            |
| da (min)              | 91 mm            |
| Da (max)              | 108 mm           |
| ra (max)              | 1.5 mm           |