

# 30TAB06DF NACHI Dynamic Load Rating 29.900 N 30x62x15mm Thrust ball bearings

|                               |                  |
|-------------------------------|------------------|
| Bearing number                | 30TAB06DF        |
| Size (mm)                     | 30x62x15         |
| Brand                         | NACHI            |
| Bore Diameter (mm)            | 30               |
| Outer Diameter (mm)           | 62               |
| Width (mm)                    | 15               |
| d                             | 30 mm            |
| D                             | 62 mm            |
| B                             | 15 mm            |
| C                             | 15 mm            |
| Angle ( $\alpha$ )            | 60 °             |
| r min.                        | 1 mm             |
| r1 min.                       | 0.6 mm           |
| 2B                            | 30 mm            |
| Weight                        | 0.21 Kg          |
| Basic dynamic load rating (C) | 29.9 kN          |
| Basic static load rating (C0) | 46.4 kN          |
| Bore Type                     | Cylindrical Bore |
| Enclosure                     | Open             |
| Configuration                 | Double Row       |
| Bore Size                     | 30 mm            |
| Outside Diameter              | 62 mm            |
| Width                         | 15 mm            |
| Fillet Radius/Chamfer         | 1 mm             |

|                                      |           |
|--------------------------------------|-----------|
| r1                                   | 0.6 mm    |
| Dynamic Load Rating                  | 29.900 N  |
| Static Load Rating                   | 46.400 N  |
| Limiting Speed – Grease              | 4.650 rpm |
| Limiting Speed – Oil                 | 6.000 rpm |
| Starting Torque – Grease Lubrication | 20 N·cm   |
| da1 (min)                            | 46.2 mm   |
| da2 (min)                            | 39.7 mm   |
| Da1 (max)                            | 46 mm     |
| Da2 (max)                            | 53.4 mm   |