

# 35TAB07DF NACHI 35x72x15mm Starting Torque – Grease Lubrication 25 N·cm Thrust ball bearings

Bearing number	35TAB07DF
Size (mm)	35x72x15
Brand	NACHI
Bore Diameter (mm)	35
Outer Diameter (mm)	72
Width (mm)	15
d	35 mm
D	72 mm
B	15 mm
C	15 mm
Angle ( $\alpha$ )	60 °
r min.	1 mm
r1 min.	0.6 mm
2B	30 mm
Weight	0.29 Kg
Basic dynamic load rating (C)	32.5 kN
Basic static load rating (C0)	54.3 kN
Bore Type	Cylindrical Bore
Enclosure	Open
Configuration	Double Row
Bore Size	35 mm
Outside Diameter	72 mm

Width	15 mm
Fillet Radius/Chamfer	1 mm
r1	0.6 mm
Dynamic Load Rating	32.500 N
Static Load Rating	54.300 N
Limiting Speed – Grease	3.750 rpm
Limiting Speed – Oil	5.000 rpm
Starting Torque – Grease Lubrication	25 N·cm
da1 (min)	56.2 mm
da2 (min)	49.7 mm
Da1 (max)	56 mm
Da2 (max)	63.4 mm