

# 40TAB07 NACHI Da2 (max) 63.4 mm 40x72x15mm Thrust ball bearings

Bearing number	40TAB07
Size (mm)	40x72x15
Brand	NACHI
Bore Diameter (mm)	40
Outer Diameter (mm)	72
Width (mm)	15
d	40 mm
D	72 mm
B	15 mm
C	15 mm
Angle ( $\alpha$ )	60 °
r min.	1 mm
r1 min.	0.6 mm
Weight	0.26 Kg
Basic dynamic load rating (C)	32.5 kN
Basic static load rating (C0)	54.3 kN
(Grease) Lubrication Speed	3750 r/min
Enclosure	Open
Configuration	Single Row
Bore Type	Cylindrical Bore
Bore Size	40 mm
Outside Diameter	72 mm
Width	15 mm
Fillet Radius/Chamfer	1 mm

r1	0.6 mm
a	0 mm
2B	30 mm
Dynamic Load Rating	32.500 N
Static Load Rating	54.300 N
Limiting Speed – Grease	3.750 rpm
Limiting Speed – Oil	5.000 rpm
Starting Torque – Grease Lubrication	25 N·cm
da1 (min)	56.2 mm
da2 (min)	49.7 mm
Da1 (max)	56 mm
Da2 (max)	63.4 mm