

4426 INA

52.388×80.98×22.225mm Weight / Kilogram 0.42 Thrust ball bearings

| | |
|---------------------|--|
| Bearing number | 4426 |
| Size (mm) | 52.388×80.98×22.225 |
| Brand | INA |
| Bore Diameter (mm) | 52.388 |
| Outer Diameter (mm) | 80.98 |
| Width (mm) | 22.225 |
| d | 2 1/16 inch |
| d | 52.388 mm |
| D | 3.188 inch |
| D | 80.98 mm |
| T | 0.875 inch |
| T | 22.225 mm |
| D ₁ | 53.188 mm |
| D ₁ | 2.094 inch |
| m | 0.917 lbs / Weight |
| m | 0.416 kg / Weight |
| C _a | 6970 lbf / Dynamic load rating (axial) |
| C _a | 31000 N / Dynamic load rating (axial) |
| C _{0a} | 17300 lbf / Static load rating (axial) |
| C _{0a} | 77000 N / Static load rating (axial) |

| | |
|----------------------------|--|
| Category | Thrust Ball Bearing |
| BDI Inventory | 0.0 |
| Manufacturer Name | SCHAEFFLER GROUP |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.42 |
| EAN | 4012802029680 |
| Product Group – BDI | B00308 |
| Rolling Element | Ball Bearing |
| Thrust Bearing | Yes |
| Single or Double Direction | Single Direction |
| Banded | No |
| Cage Material | Steel |
| Precision Class | ABEC 1 ISO P0 |
| Component Description | Roller Assembly Plus Raceways |
| Other Features | Single Row Deep Groove Medium Cross Section Grooved Race Separable |
| Long Description | 2-1/16" Bore 1; 2-3/32" Bore 2; 3-3/16" Outside Diameter; 7/8" Height; Ball Bearing; Single Direction; Not Banded; Steel Cage; ABEC 1 ISO P0 Precision |
| Inch – Metric | Inch |
| Category – BDI | Thrust Ball Bearings |
| UNSPSC | 31171507 |
| Harmonized Tariff Code | 8482.10.50.08 |
| Noun | Bearing |
| Keyword String | Ball Thrust |
| Manufacturer URL | http://www.ina.com |

| | |
|-------------------------------------|--------------------------------|
| Manufacturer Item Number | 4426 |
| Weight / LBS | 0.917 |
| Outside Diameter | 3.188 Inch 80.975 Millimeter |
| Height | 0.875 Inch 22.225 Millimeter |
| Bore 2 | 2.094 Inch 53.188 Millimeter |
| Bore 1 | 2.063 Inch 52.4 Millimeter |
| Overall Height with Aligning Washer | 0 Inch 0 Millimeter |