

51117 SKF 85x110x19mm bearings

**Width 19mm
Thrust ball**

| | |
|-------------------------------|---------------------|
| Bearing number | 51117 |
| Size (mm) | 85x110x19 |
| Brand | SKF |
| Bore Diameter (mm) | 85 |
| Outer Diameter (mm) | 110 |
| Width (mm) | 19 |
| d | 85 mm |
| D | 110 mm |
| H | 19 mm |
| d1 | 110 mm |
| r1 min. | 1 mm |
| r2 min. | 1 mm |
| D1 | 87 mm |
| da min. | 100 mm |
| Da max. | 95 mm |
| ra max. | 1 mm |
| Weight | 0.44 Kg |
| Basic dynamic load rating (C) | 44.9 kN |
| Basic static load rating (C0) | 146 kN |
| Fatigue load limit (Pu) | 5.4 |
| Reference speed | 3000 r/min |
| Limiting speed | 4300 r/min |
| Category | Thrust Ball Bearing |
| BDI Inventory | 0.0 |

| | |
|-------------------------------------|--|
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.45 |
| EAN | 7316576677731 |
| Product Group – BDI | B00308 |
| Rolling Element | Ball Bearing |
| Thrust Bearing | Yes |
| Single or Double Direction | Single Direction |
| Banded | No |
| Cage Material | Steel |
| Precision Class | ABEC 1 ISO P0 |
| Component Description | Roller Assembly Plus Raceways |
| Other Features | Single Row |
| Long Description | 85MM Bore 1; 87MM Bore 2; 110MM Outside Diameter; 19MM Height; Ball Bearing; Single Direction; Not Banded; Steel Cage; ABEC 1 ISO P0 Precision |
| Inch – Metric | Metric |
| Category – BDI | Thrust Ball Bearings |
| UNSPSC | 31171507 |
| Harmonized Tariff Code | 8482.10.50.08 |
| Noun | Bearing |
| Keyword String | Ball Thrust |
| Manufacturer URL | http://www.skf.com |
| Manufacturer Item Number | 51117 |
| Weight / LBS | 0.992 |
| Bore 1 | 3.346 Inch 85 Millimeter |
| Overall Height with Aligning Washer | 0 Inch 0 Millimeter |

| | |
|---|-----------------------------|
| Bore 2 | 3.425 Inch 87 Millimeter |
| Height | 0.748 Inch 19 Millimeter |
| Outside Diameter | 4.331 Inch 110 Millimeter |
| bore diameter: | 85 mm |
| static load capacity: | 146 kN |
| outside diameter: | 110 mm |
| dynamic load capacity: | 44.9 kN |
| overall width: | 19 mm |
| maximum rpm: | 4300 RPM |
| thrust bearing type: | Single-Direction |
| cage material: | Steel |
| outside diameter design: | Straight |
| fillet radius: | 1 mm |
| separable or banded: | Separable |
| series: | 511 |
| precision rating: | Not Rated |
| $d_1 \approx$ | 110 mm |
| $D_1 \approx$ | 87 mm |
| $r_{1,2} \text{ min.}$ | 1 mm |
| $d_a \text{ min.}$ | 100 mm |
| $D_a \text{ max.}$ | 95 mm |
| $r_a \text{ max.}$ | 1 mm |
| Basic dynamic load rating C | 44.9 kN |
| Basic static load rating C_0 | 146 kN |
| Fatigue load limit P_u | 5.4 kN |
| Minimum load factor A | 0.14 |
| Mass bearing (including seat washer where applicable) | 0.44 kg |