

# 51160X NSK 300x380x62mm D\_a 332 Thrust ball bearings

Bearing number	51160X
Size (mm)	300x380x62
Brand	NSK
Series	
DIa (mm)	300
DIe (mm)	380
Width (mm)	62
d	300 mm
D	380 mm
T	62 mm
d1	376 mm
r min.	2 mm
D1	304 mm
d2 min.	348 mm
D2 max.	332 mm
ra max.	2 mm
Weight	17.2 Kg
Basic dynamic load rating (C)	360 kN
Basic static load rating (C0)	1560 kN
(Grease) Lubrication Speed	600 r/min
SRI	15.43
NSK Code	51160X
D	380
SREX	0.1
C	360
d	62
CAD	<a href="http://service.web3cad.co.jp/pcom/?Maker=NSK_PBSinfo=nsk_rb/roller_bearings/thrust_bearings/single_direction_tbb/with_flat_seet_asmtab.prj&amp;varset={ORDER=51160X},{SD=300},{D=380},{T=62},{SR=2.0},{CAN=3600000},{COM=1560000},{CA=36500},{COM=1560000},{GRE=600},{DIL=900},{S01=376},{D1=304},{D2A=348},{D2=332},{SRA=2.0},{MSS=17.200}">http://service.web3cad.co.jp/pcom/?Maker=NSK_PBSinfo=nsk_rb/roller_bearings/thrust_bearings/single_direction_tbb/with_flat_seet_asmtab.prj&amp;varset={ORDER=51160X},{SD=300},{D=380},{T=62},{SR=2.0},{CAN=3600000},{COM=1560000},{CA=36500},{COM=1560000},{GRE=600},{DIL=900},{S01=376},{D1=304},{D2A=348},{D2=332},{SRA=2.0},{MSS=17.200}</a>
h4table	ecat_NSK0TB
Oil rpm	900
SRI	15.43
max	17.2
GRS rpm	600
ra	2
SREX	0.1
D a	332
SRI2	0
C0	1560
SREN	0
D-1	304
Prod_Type3	TR_50_MFS
da	348
da	28.575
Z	31
y04	51160X
SRE	340
r	2
T	62
KBRG	511
calcort	/bearingGuide/html/calculation.jsp