

# 51168X NSK 340x420x64mm D\_420 Thrust ball bearings

Bearing number	51168X
Size (mm)	340x420x64
Brand	NSK
Series	
DIa (mm)	340
DIo (mm)	420
Width (mm)	64
d	340 mm
D	420 mm
T	64 mm
d1	416 mm
r min.	2 mm
D1	344 mm
d1 min.	388 mm
D1 max.	372 mm
ra max.	2 mm
Weight	19.9 Kg
Basic dynamic load rating (C)	375 kN
Basic static load rating (C0)	1760 kN
(Grease) Lubrication Speed	560 r/min
SRL	15.43
NSK code	51168X
D	420
SRLX	0.1
C	375
D1	64
CAD	<a href="http://service.web3cad.co.jp/pcom/?Maker=NSK_PBSinfo=nsk_rb/roller_bearings/thrust_bearings/single_direction_tbb/with_flat_seet_asmtab.prj&amp;varset={ORDER=51168X,(D=420),(T=64),(SR=2.0),(CAN=375000),(COM=1760000),(CA=38500),(COM=170000),(GRE=560),(D1=416),(D1=344),(D1=388),(DA=372),(SRA=2.0),(MSS=19.900)}">http://service.web3cad.co.jp/pcom/?Maker=NSK_PBSinfo=nsk_rb/roller_bearings/thrust_bearings/single_direction_tbb/with_flat_seet_asmtab.prj&amp;varset={ORDER=51168X,(D=420),(T=64),(SR=2.0),(CAN=375000),(COM=1760000),(CA=38500),(COM=170000),(GRE=560),(D1=416),(D1=344),(D1=388),(DA=372),(SRA=2.0),(MSS=19.900)}</a>
h4fTable	ecat_N50TB
Oil rpm	850
SRL	15.43
max	19.9
GRS rpm	560
ra	2
SRLX	0.1
D1	372
SRLZ	0
C0	1760
SREN	0
D-1	344
Prod_Type3	TR_50_MFS
da	388
da	28.575
Z	35
y0L	51168X
SRL	388
r	2
T	64
KBRG	511
calcort	/bearingGuide/html/calculation.jsp