

# AST 22312CYW33 spherical roller bearings

How 0.0 Inventory do TIMKEN Manufacturer Name you find the AST 22312CYW33 spherical roller bearings specification? Manufacturers Online Free check

|                           |                                    |
|---------------------------|------------------------------------|
| Inventory                 | 0.0                                |
| Manufacturer Name         | TIMKEN                             |
| Minimum Buy Quantity      | N/A                                |
| Weight                    | 22.7                               |
| EAN                       | 0883450205092                      |
| Product Group             | M06288                             |
| Number of Mounting Holes  | 2                                  |
| Mounting Method           | V Lock                             |
| Housing Style             | 2 Bolt Pillow Block                |
| Rolling Element           | Spherical Roller Bearing           |
| Housing Material          | Cast Steel                         |
| Expansion / Non-expansion | Non-expansion                      |
| Mounting Bolts            | 20 Millimeter                      |
| Relubricatable            | Yes                                |
| Insert Part Number        | 22219                              |
| Seals                     | Triple Lip Viton                   |
| Housing Configuration     | 1 Piece Solid                      |
| Inch – Metric             | Metric                             |
| Other Features            | Double Row   Single Nut   SN Style |

|                               |  |
|-------------------------------|--|
| Long Description              | 2 Bolt Pillow Block; 80MM Bore; 100MM Base to Center Height; V Lock Mount; Spherical Roller Bearing; |
| UNSPSC                        | 31171511   |
| Harmonized Tariff Code        | 8483.20.40.80  |
| Noun                          | Bearing  |
| Keyword String                | Pillow Block   |
| Manufacturer Item Number      | QVSN19V080SN   |
| Weight / LBS                  | 50   |
| D                             | 3.661 Inch   93 Millimeter   |
| B                             | 3.937 Inch   100 Millimeter  |
| d                             | 3.15 Inch   80 Millimeter  |
| Bolt Spacing Maximum          | 11.496 Inch   292Millimeter  |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter   |
| Nominal Bolt Center to Center | 11.3 Inch   287 Millimeter   |
| Bolt Spacing Minimum          | 11.024 Inch   280Millimeter  |