

# AST 7030C angular contact ball bearings

are a 0.0 Inventory few brands you will find in our inventory. Find AST 7030C angular contact ball bearings to see what's in stock!

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	6.13
EAN	7316577026224
Product Group	M06288
Number of Mounting Holes	4
Mounting Method	Concentric Collar
Housing Style	4 Bolt Round Flange Cartridge
Rolling Element	Spherical Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	1/2 Inch
Relubricatable	Yes
Insert Part Number	22213
Seals	Garter Spring
Housing Configuration	1 Piece Solid
Pilot Configuration	With Pilot
Inch – Metric	Inch

Long Description	4 Bolt Round Flange Cartridge; 2-1/2" Bore; 6-1/2" Bolt Circle; 4.6" Bolt Spacing; 1
Other Features	Double Row   Heavy Duty   Open End   With Set Screw
UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Flanged
Manufacturer Item Number	FYRP 2.1/2 H-3
Weight / LBS	13.5
Cartridge Pilot Depth	1 Inch   25.4 Millimeter
d	2.5 Inch   63.5 Millimeter
Nominal Bolt Circle Diameter Round	6.5 Inch   165 Millimeter
Cartridge Pilot Diameter	5.5 Inch   139.7 Millimeter
D	3.375 Inch   85.725 Millimeter
Bolt Spacing	4.6 Inch   117 Millimeter
bore diameter:	2-1/2 in
expansion type:	Non-Expansion Bearing (Fixed)
bolt center-to-center length:	4.0600 in
seal type:	Radial Shaft Seal
bolt circle diameter:	6-1/2 in
overall depth:	3-1/2 in
overall length/diameter:	7.6250 in
radial dynamic load capacity:	33300 lb
flange mounting type:	Four-Bolt Piloted

radial static load capacity:	41100 lb
bearing type:	Spherical Roller
operating temperature range:	-5 to +230 °F
housing construction:	Solid Flange Mount
maximum rpm:	1100 RPM
bore type:	Round
finish/coating:	Uncoated
duty type:	Standard Duty
lubrication type:	Lubrication Fitting
housing material:	Cast Iron
series:	222
locking device:	Set Screw