

AST AST090 11080 plain bearings

AST AST090 11080 plain bearings Warehouse offers car parts and car accessories. We sell discount 131.762 mm da online as well 117.805 mm Ca as cheap machinery parts.

| | |
|---------|---------------|
| da | 131.762 mm |
| Da | 319.999 mm |
| Ca | 117.805 mm |
| A1 | 180.975 mm |
| A2 | 317.5 mm |
| S | 4.763 mm |
| ba | 83.344 mm |
| H | 377.825 mm |
| H1 | 190.5 mm |
| H2 | 76.2 mm |
| J min. | 530.225 mm |
| J max. | 600.075 mm |
| J1 | 117.475 mm |
| L | 679.45 mm |
| N1 | 28.575 mm |
| R1 | 114.3 mm |
| R2 | 41.275 mm |
| RG | 3/4 NPT |
| PG | 1/4 NPT |
| h | 66.675 mm |
| Housing | SAF 630 |
| Bearing | 22330 CCK/W33 |

| | |
|--|----------------|
| Adapter sleeve assembly | SNW 130×5.3/16 |
| Stabilizing ring | SR-36-30 |
| Taconite seal | TER 125 |
| End plug (suffix Y) | EPR 17 |
| Max. speed for Taconite seal | 590 r/min |
| P60° | 234 kN |
| P90° | 140 kN |
| P120° | 84.5 kN |
| P150° | 75.6 kN |
| P180° | 89 kN |
| Pa | 48.9 kN |
| Mass pillow block | 146 kg |
| Cap bolt | 4 x 3/4-10 UNC |
| Cap bolt recommended tightening torque | 203.4 N·m |
| Cap bolt, SAE grade | 5 |
| Eye bolt | 2 x 3/8-16 UNC |
| Appropriate attachment bolt size G | 1 in |
| Initial grease fill | 1304.1 g |