

# AST AST090 1815 plain bearings

Online shopping AST AST090 1815 plain bearings 15x28x7 Size (mm) from a great selection at 15 Bore Diameter (mm) Store. ... Accessories.

Size (mm)	15x28x7
Bore Diameter (mm)	15
Outer Diameter (mm)	28
Width (mm)	7
d	15 mm
D	28 mm
B	7 mm
C	7 mm
r min.	0,3 mm
da min.	17 mm
da max	17 mm
Da max.	26 mm
ra max.	0,3 mm
Weight	0,015 Kg
Basic dynamic load rating (C)	4,35 kN
Basic static load rating (C0)	2,26 kN
(Grease) Lubrication Speed	26 000 r/min
Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	0.01
EAN	0029176026751

Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Non-Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	15MM Bore; 28MM Outside Diameter; 7MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1   ISO P0; N
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6902VV
Weight / LBS	0.016
Outside Diameter	1.102 Inch   28 Millimeter
Outer Race Width	0.276 Inch   7 Millimeter
Bore	0.591 Inch   15 Millimeter
bore diameter:	15 mm
static load capacity:	2260 N
outside diameter:	28 mm
precision rating:	ABEC 1 (ISO Class Normal)
overall width:	7 mm
finish/coating:	Uncoated

bore type:	Round
cage material:	Steel
closure type:	Double Sealed
outer ring width:	7 mm
row type & fill slot:	Single Row Non-Fill Slot
fillet radius:	0.3 mm
internal clearance:	C0
maximum rpm:	26000 RPM
operating temperature range:	-10 to +110 °C
series:	69
dynamic load capacity:	4350 N
SRI	2.05
hidYobi	6902VV
LangID	1
D_	28
SREX	0.015
B_	7
da min	17
hidTable	ecat_NSRDGB
SRE	2.05
mass	0.015
GRS rpm	26000
ra	0.3
SRIX	0.015
D_a	26
SRIN	-0.015
C0	2.26
fo	14.3
SREN	-0.015

DE_	25.469
Prod_Type3	DGBB_SR_VV
DA_	3.969
bomp	0
Z_	10
yobi	6902VV
C_conv	4350
ALPHA_	0
SDM_	21.5
r	0.3
KBRG	6151
SBRG	19
DI_	17.531