

# AST AST11 1515 plain bearings

Request A Quote For Your Special AST AST11 1515 plain bearings Needs Today! Free 0.0 Inventory Quotes. ISO 9001 certified. TIMKEN Manufacturer Name

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | TIMKEN  |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 14.528  |
| EAN                       | 0883450354257   |
| Product Group             | M06288  |
| Number of Mounting Holes  | 2   |
| Mounting Method           | Concentric Collar   |
| Housing Style             | 2 Bolt Pillow Block   |
| Rolling Element           | Spherical Roller Bearing  |
| Housing Material          | Cast Steel  |
| Expansion / Non-expansion | Non-expansion   |
| Mounting Bolts            | 3/4 Inch  |
| Relubricatable            | Yes   |
| Insert Part Number        | 22215   |
| Seals                     | Triple Lip Viton  |
| Housing Configuration     | 1 Piece Solid   |
| Inch – Metric             | Inch  |
| Other Features            | Double Row   Single Collar   SN Style   With Set Screw                                    |
| Long Description          | 2 Bolt Pillow Block; 2-11/16" Bore; 3.74" Base to Center Height; Concentric Collar Mount; |
| UNSPSC                    | 31171511  |

|                               |                                |
|-------------------------------|--------------------------------|
| Harmonized Tariff Code        | 8483.20.40.80                  |
| Noun                          | Bearing                        |
| Keyword String                | Pillow Block                   |
| Manufacturer Item Number      | QASN15A211SN                   |
| Weight / LBS                  | 46                             |
| Bolt Spacing Minimum          | 9.49 Inch   241.046Millimeter  |
| Bolt Spacing Maximum          | 10.98 Inch   278.892Millimeter |
| D                             | 3.62 Inch   91.948 Millimeter  |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter           |
| Nominal Bolt Center to Center | 10.2 Inch   260 Millimeter     |
| B                             | 3.74 Inch   95 Millimeter      |
| d                             | 2.688 Inch   68.275 Millimeter |