

AST AST40 F30160 plain bearings

Online 320 Outer Diameter (mm) shopping AST AST40 F30160 plain bearings 190x320x104 Size (mm) from a great selection at Store. ... Accessories. 190 Bore Diameter (mm)

Size (mm)	190x320x104
Bore Diameter (mm)	190
Outer Diameter (mm)	320
Width (mm)	104
d	190 mm
D	320 mm
B	104 mm
C	104 mm
r min.	3 mm
da min.	204 mm
da max	219 mm
Da min	276 mm
Da max.	306 mm
ra max.	2,5 mm
Weight	34,5 Kg
Basic dynamic load rating (C)	1190 kN
Basic static load rating (C0)	2020 kN
(Grease) Lubrication Speed	850 r/min
(Oil) Lubrication Speed	1100 r/min
Calculation factor (e)	0,31
Calculation factor (Y0)	2,2
Calculation factor (Y2)	3,3

Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	33
EAN	0029176037610
Product Group	B04311
Internal Clearance	C0-Medium
Mounting Method	Adapter Mount
Rolling Element	Spherical Roller Bearing
Bore Profile	Tapered
Cage Material	Steel
Enclosure	Open
Number of Rows of Rollers	Double Row
Relubricatable	Yes
Withdrawal Sleeve	AH3138 (Specify bore)
Inch – Metric	Metric
Long Description	190MM Tapered Bore; 320MM Outside Diameter; 104MM Width; C0-Medium Clearance; Adapter Mount; Double
Other Features	Order adapter or withdrawal sleeve or nut separately. Others may be available
UNSPSC	31171510
Harmonized Tariff Code	84823080
Noun	Bearing
Keyword String	Spherical
Manufacturer Item Number	23138CKE4
Weight / LBS	33
Width	4.094 Inch 104 Millimeter

Adapter Part Number	SNW3138 H3138 HA3138 HE3138 (Specify bore) Inch H3138 (Specify bore) Millimeter
Outside Diameter	12.598 Inch 320 Millimeter
Bore	7.48 Inch 190 Millimeter
Y3	2.2
hidYobi	23138CKE4
LangID	1
Y1	2.2
D_	320
Y2	3.3
Macha rpm	0
B_	104
da min	204
hidTable	ecat_NSSPHR
Oil rpm	1100
Y0	2.2
mass	34.5
GRS rpm	850
ra	2.5
TSR rpm	1600
C0	2020
DE_	287.118
X0	1
Prod_Type3	SRB_CTB_TB
X1	1
X2	0.67
SIR	42
e	0.31

DA_	31.5
bomp	23138CKE4
Z_	21
ALP2	30
ALP1	11
ALP3	0
D_a max	306
D_a min	276
yobi	23138CKE4
ALPHA_	0.201
SDM_	256.25
r	3
KBRG	2322
SBRG	31
DI_	225.383