

AST AST50 92IB76 plain bearings

AST AST50 92IB76 plain bearings SEARCH SKF Manufacturer Name – Whether it's agriculture or N/A Minimum Buy Quantity construction equipment your working on, 0.0 Inventory Has the you need.

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	50.946
EAN	7316576602412
Product Group	B04311
Internal Clearance	C3-Loose
Mounting Method	Adapter Mount
Rolling Element	Spherical Roller Bearing
Bore Profile	Tapered
Cage Material	Steel
Enclosure	Open
Number of Rows of Rollers	Double Row
Relubricatable	Yes
Withdrawal Sleeve	AH2332 (Specify bore)
Withdrawal Nut	KM36
Inch – Metric	Metric
Long Description	160MM Tapered Bore; 340MM Outside Diameter; 114MM Width; C3-Loose Clearance; Adapter Mount; Double R

Other Features	Order adapter or withdrawal sleeve or nut separately. Others may be available
UNSPSC	31171510
Harmonized Tariff Code	84823080
Noun	Bearing
Keyword String	Spherical
Weight / LBS	112.215
D	13.386 Inch 340 Millimeter
B	4.488 Inch 114 Millimeter
d	6.299 Inch 160 Millimeter
Adapter Part Number	SNW132 H2332 HA2332 HE2332 (Specify bore) Inch H2332 (Specify bore) Millimeter
bore diameter:	160 mm
maximum rpm:	1900 RPM
outside diameter:	340 mm
operating temperature range:	Maximum of +390 °F
overall width:	114 mm
cage material:	Steel
bore type:	Tapered 1:12
bearing material:	Steel
outer ring type:	Not Split
cage type:	Inner Ring Guided
internal clearance:	C3
precision rating:	Not Rated
closure type:	Open
finish/coating:	Uncoated
lubrication hole type:	Lubrication Groove & Hole
outer ring width:	114 mm

dynamic load capacity:	1600 kN
fillet radius:	3 mm
static load capacity:	1960 kN
series:	223