

AST AST850SM 5050 plain bearings

AST AST850SM 5050 plain bearings 24 mm C Product Brochures , Manufacturing Service . Get Your Free. 47 mm D

D	47 mm
d1	20 mm
C	24 mm
F	25.5 mm
B	25.5 mm
B1	66 mm
B2	40.5 mm
G	M20X1.5
G1	21 mm
B3	9 mm
C1	0.8 mm
n	8 mm
a	4 mm
e	27 mm
h	8 mm
Dw	5 mm
Lw	8 mm
Maximum tightening torque	98 Nm
Bearing with/without cage	Sans
Radial clearance class	CN
Precision class	P0
Mass	0.38 kg
Cr	38.5 kN

C0r	48 kN
Track load capacity cylindrical outer ring	21 kN
Nlim (grease)	4,000 rpm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	5.94 Hz
Characteristic outer ring frequency, BPF0	7.94 Hz
Characteristic inner ring frequency, BRFI	11.06 Hz
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.464
Product Group	B04120