

AST F602XH deep groove ball bearings

Shop AST F602XH deep groove ball bearings huge online discount inventory. and Import machinery parts your car 95x170x32 Size (mm) needs with Free Shipping and 170 Outer Diameter (mm) Free Extended Warranty.

Size (mm)	95x170x32
Bore Diameter (mm)	95
Outer Diameter (mm)	170
Width (mm)	32
d	95 mm
D	170 mm
B	32 mm
C	32 mm
Angle (α)	40 °
a	71,5 mm
r min.	2,1 mm
r1 min.	1,1 mm
da min.	107 mm
db min	102 mm
ra max.	2 mm
Weight	2,72 Kg
Basic dynamic load rating (C)	121 kN
Basic static load rating (C0)	107 kN
(Grease) Lubrication Speed	3 500 r/min
Contact angle α	40 °
rs min	2.1 mm

r1s min	1.1 mm
Mass	2.72 kg
Dynamic load, C	121 kN
Static load, C0	107 kN
Fatigue limit load, Cu	4.25 kN
Nlim (oil)	4,700 rpm
Nlim (grease)	3,500 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
da min	107 mm
Da max	158 mm
Db max	163 mm
r1a max	1 mm
ra max	2 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	2.74
Product Group	B00308
Enclosure	Open
Flush Ground	No
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Steel
Contact Angle	40 Degree
Internal Clearance	C0-Medium

Number of Bearings	1 (Single)
Inch – Metric	Metric
Long Description	95MM Bore; 170MM Outside Diameter; 32MM Width; Open; No Flush Ground; Ball Bearing; Single Row of Ba
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Outside Diameter	6.693 Inch 170 Millimeter
Bore	3.74 Inch 95 Millimeter
Width	1.26 Inch 32 Millimeter