

AST F693H deep groove ball bearings

What 24x15x23 Size (mm) is the 24 Bore Diameter (mm) best place to buy AST F693H deep groove ball bearings online? Manufacturing Service . 15 Outer Diameter (mm)

Size (mm)	24x15x23
Bore Diameter (mm)	24
Outer Diameter (mm)	15
Width (mm)	23
Fw	15 mm
D	24 mm
C	23 mm
C1	9 mm
C2	6.5 mm
d	15 mm
D1	28.1 mm
r1,2 – min.	0.3 mm
da – min.	23.7 mm
ra – max.	0.3 mm
rb – max.	0.3 mm
di	12 mm
F	15 mm
Bi	16 mm
Basic dynamic load rating, radial direction – C	11 kN
Basic static load rating, radial direction – C0	14 kN

Basic dynamic load rating, axial direction – C	10.6 kN
Basic static load rating, axial direction – C0	18.3 kN
Fatigue load limit, radial direction – Pu	1.7 kN
Fatigue load limit, axial direction – Pu	0.67 kN
Reference speed	8500 r/min
Limiting speed	12000 r/min
Mass bearing	0.044 kg
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.044
EAN	7316577014689
Product Group	B04144
bore diameter:	15 mm
axial static load capacity:	18.3 kN
outside diameter:	28 mm
maximum rpm:	12000 rpm
overall width:	23 mm
closure type:	Open
bearing type:	Needle Roller/Axial Ball Bearing
radial bearing outside diameter:	28.10 mm
operating temperature range:	0 to 250 °F
fillet radius:	0.3 mm
radial dynamic load capacity:	11 kN
series:	NKX

radial static load capacity:	14 kN
manufacturer product page:	Click here
axial dynamic load capacity:	10.6 kN
manufacturer upc number:	7316577014689
bearing material:	Steel
weight:	0.097 lbs
r1,2 min.	0.3 mm
da min.	23.7 mm
ra max.	0.3 mm
rb max.	0.3 mm
Basic dynamic load rating, radial direction C	11 kN
Basic static load rating, radial direction C0	14 kN
Basic dynamic load rating, axial direction C	10.6 kN
Basic static load rating, axial direction C0	18.3 kN
Fatigue load limit, radial direction Pu	1.66 kN
Fatigue load limit, axial direction Pu	0.67 kN
Minimum axial load factor A	0.0017
Inner ring	IR 12x15x16