

# AST GEH200HC plain bearings

AST GEH200HC plain bearings Manufacturers , Online N/A Minimum Buy Quantity Wholesale Suppliers ! 0.0 Inventory

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 22.246   |
| EAN                       | 0883450298407  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Concentric Collar  |
| Housing Style             | 2 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Steel   |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 1 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 22220  |
| Seals                     | Triple Lip Nitrile Rubber  |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Metric   |
| Other Features            | Double Row   Single Collar   With Set Screw  |
| Long Description          | 2 Bolt Pillow Block; 100MM Bore; 104.8MM Base to Center Height; Concentric Collar Mount; Spherical R |
| UNSPSC                    | 31171511   |

|                               |                                |
|-------------------------------|--------------------------------|
| Harmonized Tariff Code        | 8483.20.40.80                  |
| Noun                          | Bearing                        |
| Keyword String                | Pillow Block                   |
| Weight / LBS                  | 59                             |
| Nominal Bolt Center to Center | 11.3 Inch   287 Millimeter     |
| D                             | 4.6 Inch   116.84 Millimeter   |
| Bolt Spacing Maximum          | 12.6 Inch   320.04Millimeter   |
| d                             | 3.937 Inch   100 Millimeter    |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter           |
| B                             | 4.126 Inch   104.8 Millimeter  |
| Bolt Spacing Minimum          | 10.04 Inch   255.016Millimeter |