

AST JL68145/JL6811Z tapered roller bearings

offers a AST JL68145/JL6811Z tapered roller bearings selection of Genuine at Wholesale Prices. We are a 40 mm d 80 mm D AST JL68145/JL6811Z tapered roller bearings Certified 23 mm B Parts Retailer

d	40 mm
D	80 mm
B	23 mm
E	71.5 mm
F	49.5 mm
d1	53.9 mm
rs min	1.1 mm
rls min	1.1 mm
Radial clearance class	CN
Mass (without HJ ring)	0.53 kg
Dynamic load, C	72.5 kN
Static load, C0	77.5 kN
Fatigue limit load, Cu	9.5 kN
Nlim (oil)	8,900 rpm
Nlim (grease)	7,600 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.41 Hz
Characteristic rolling element frequency, BSF	5.32 Hz
Characteristic outer ring frequency, BPF0	5.73 Hz
Characteristic inner ring frequency, BRFI	8.27 Hz

da min	46.5 mm
da max	49 mm
dc min	56 mm
Da max	73.5 mm
ra max	1 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.527
Product Group	B04144