

# AST NJ2315 EM cylindrical roller bearings

AST NJ2315 EM cylindrical roller bearings manufacturer and global supplier of reliable ball and roller ... AST NJ2315 EM cylindrical roller bearings Industries 0.0 Inventory Products Manufacturing & Engineering and Agricultural Bearings designed to meet the N/A Minimum Buy Quantity unique requirements of TIMKEN Manufacturer Name our targeted industries.

|                           |                          |
|---------------------------|--------------------------|
| Inventory                 | 0.0                      |
| Manufacturer Name         | TIMKEN                   |
| Minimum Buy Quantity      | N/A                      |
| Weight                    | 10.442                   |
| EAN                       | 0883450113205            |
| Product Group             | M06288                   |
| Number of Mounting Holes  | 2                        |
| Mounting Method           | V Lock                   |
| Housing Style             | 2 Bolt Pillow Block      |
| Rolling Element           | Spherical Roller Bearing |
| Housing Material          | Cast Steel               |
| Expansion / Non-expansion | Expansion                |
| Mounting Bolts            | 3/4 Inch                 |
| Relubricatable            | Yes                      |
| Insert Part Number        | 22216                    |
| Seals                     | Teflon Labyrinth         |
| Housing Configuration     | 1 Piece Solid            |
| Inch – Metric             | Inch                     |
| Other Features            | Double Row   Single Nut  |

|                               |  |
|-------------------------------|--|
| Long Description              | 2 Bolt Pillow Block; 2-3/4" Bore; 3-1/4" Base to Center Height; V Lock Mount; Spherical Ro |
| UNSPSC                        | 31171511   |
| Harmonized Tariff Code        | 8483.20.40.80  |
| Noun                          | Bearing  |
| Keyword String                | Pillow Block   |
| Manufacturer Item Number      | QVPL16V212SET  |
| Weight / LBS                  | 23   |
| Nominal Bolt Center to Center | 8.1 Inch   206.4 Millimeter  |
| B                             | 3.25 Inch   82.55 Millimeter   |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter   |
| D                             | 3.29 Inch   83.566 Millimeter  |
| Bolt Spacing Minimum          | 7.7 Inch   195.58Millimeter  |
| Bolt Spacing Maximum          | 8.4 Inch   213.36Millimeter  |
| d                             | 2.75 Inch   69.85 Millimeter   |