

AST UCF 207-23E bearing units

Request A 75 mm da Quote For Your Special AST UCF 207-23E bearing units Needs Today! Free Quotes. ISO 9001 certified.

da	75 mm
db	87.313 mm
dc	71.438 mm
Da	160 mm
Ca	64.795 mm
A1	98.425 mm
A2	149.225 mm
ba	35.719 mm
H	192.088 mm
H1	101.6 mm
H2	41.275 mm
J min.	263.525 mm
J max.	295.275 mm
J1	53.975 mm
L	349.25 mm
N1	19.05 mm
R1	60.325 mm
R2	27.94 mm
RG	3/8 NPT
PG	1/8 NPT
h	42.862 mm
Housing	FSAF 315
Bearing	1315
Lock nut	AN 15

Lock washer	W 15
Stabilizing ring	2 x SR-1615
Labyrinth ring (db shaft position)	LOR 79
Labyrinth ring (dc shaft position)	LOR 46
End plug (suffix Y)	EPR 8
Bearing limiting speed	5600 r/min
P60°	101 kN
P90°	60.9 kN
P120°	38.3 kN
P150°	34.7 kN
P180°	42.3 kN
Pa	27.1 kN
Mass pillow block	20 kg
Cap bolt	2 x 5/8-11 UNC
Cap bolt recommended tightening torque	298.3 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.625 in
Initial grease fill	286.33 g