

AST UCF 208-24E bearing units

AST UCF 208-24E bearing units Needs Analysis , Manufacturing Service 35 Outer Diameter (mm) . Get Your Free. 15x35x15.9 Size (mm)

| | |
|-------------------------------|-----------------|
| Size (mm) | 15x35x15.9 |
| Bore Diameter (mm) | 15 |
| Outer Diameter (mm) | 35 |
| Width (mm) | 15,9 |
| d | 15 mm |
| D | 35 mm |
| B | 15,9 mm |
| C | 15,9 mm |
| a | 16,3 mm |
| r min. | 0,6 mm |
| da min. | 19 mm |
| da max | 19 mm |
| Da max. | 31 mm |
| ra max. | 0,6 mm |
| Basic dynamic load rating (C) | 8,5 kN |
| Basic static load rating (C0) | 5,3 kN |
| Inventory | 0.0 |
| Manufacturer Name | NTN |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0 |
| EAN | 4547359535761 |
| Product Group | B00152 |
| Enclosure | 2 Metal Shields |

| | |
|---------------------------------|--|
| Flush Ground | No |
| Rolling Element | Ball Bearing |
| Number of Rows of Balls | Double Row |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Snap Ring | No |
| Cage Material | Steel |
| Contact Angle | 25 Degree |
| Internal Clearance | C0-Medium |
| Number of Bearings | 1 (Single) |
| Inch – Metric | Metric |
| Long Description | 15MM Bore; 35MM Outside Diameter; 15.9MM Width; 2 Metal Shields; No Flush Ground; Ball Bearing; Doub |
| Other Features | Shell Alvania 2 Prelubricated |
| UNSPSC | 31171531 |
| Harmonized Tariff Code | 8482.10.50.28 |
| Noun | Bearing |
| Keyword String | Angular Contact |
| Outside Diameter | 1.378 Inch 35 Millimeter |
| Bore | 0.591 Inch 15 Millimeter |
| Width | 0.626 Inch 15.9 Millimeter |