

# Crossed Roller Slewing Bearings Without Gear Rks. 21411

What is Crossed Roller Slewing Bearings Without Gear Rks. 21411 in mechanical engineering? Manufacturing Service . Upload your CAD file for an 80.963 mm da instant.

da	80.963 mm
Da	160 mm
Ca	49.809 mm
A1	98.425 mm
A2	206.375 mm
S	4.763 mm
ba	40.481 mm
H	196.85 mm
H1	101.6 mm
H2	41.275 mm
J min.	263.525 mm
J max.	295.275 mm
L	349.25 mm
N1	23.813 mm
R1	60.325 mm
R2	27.781 mm
RG	3/8 NPT
PG	1/8 NPT
h	38.1 mm
Housing	SAFS 518

Bearing	22218 EK
Adapter sleeve assembly	SNW 18×3.3/16
Stabilizing ring	SR-18-15
Taconite seal	TER 188
End plug (suffix Y)	EPR 11
Max. speed for Taconite seal	950 r/min
P60°	141 kN
P90°	84.5 kN
P120°	53.4 kN
P150°	48 kN
P180°	58.7 kN
Pa	10.9 kN
Mass pillow block	30.8 kg
Cap bolt	1/2-13 UNC
Cap bolt recommended tightening torque	149.1 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.75 in
Initial grease fill	141.75 g