

CYSD 32006*2 tapered roller bearings

Various 20x2x8 Size (mm) 2 Outer Diameter (mm) types and sizes to accommodate your CYSD 32006*2 tapered roller bearings requirements. 20 Bore Diameter (mm)

Size (mm)	20x2x8
Bore Diameter (mm)	20
Outer Diameter (mm)	2
Width (mm)	8
d	20 mm
A1	2 mm
A2	8 mm
B	21.5 mm
B4	4.75 mm
Da – min.	51 mm
J	71.4 mm
H	8.7 mm
s1	23.5 mm
T	26 mm
Basic dynamic load rating – C	12.7 kN
Basic static load rating – C0	6.6 kN
Fatigue load limit – Pu	0.28 kN
Permissible radial housing load	max. 3.3 kN
Weight	0.34 kg
Thread – G2	M6x0.75
Hexagonal key size for grub screw – H	3 mm
Housing material	Pressed steel

Da min.	51 mm
N	8.7 mm
Basic dynamic load rating C	12.7 kN
Basic static load rating C0	6.55 kN
Fatigue load limit Pu	0.28 kN
Permissible radial housing load max.	3.3 kN
Mass unit	0.34 kg
Thread grub screw G2	M6x0.75
Hexagonal key size for grub screw N	3 mm
Recommended tightening torque for grub screw	4 N·m
Recommended diameter for attachment bolts, mm G	8 mm
Recommended diameter for attachment bolts, inch G	0.3125 in
Bearing	YET 204
Housing	PF 47