

# CYSD 4208 deep groove ball bearings

How do you find 150 mm D the CYSD 4208 deep groove ball bearings specification? Manufacturers Online Free 100 mm d check

d	100 mm
D	150 mm
B	24 mm
E	137 mm
F	113 mm
rs min	1.5 mm
r1s min	1.1 mm
Radial clearance class	C3
Mass (without HJ ring)	1.39 kg
Dynamic load, C	93 kN
Static load, C0	126 kN
Fatigue limit load, Cu	14.4 kN
Nlim (oil)	5,400 rpm
Nlim (grease)	4,600 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
da min	106.5 mm
da max	111 mm
db min	116 mm
Da max	142 mm
ra max	1.5 mm
r1a max	1 mm

Inventory	3.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	1.388
EAN	4547359137217
Product Group	B04144
Bore Profile	Straight
Cage Material	Brass
Precision Class	RBEC 1   ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring – Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C3-Loose
Retainer	Yes
Relubricatable	Yes
Inch – Metric	Metric
Other Features	Plain Inner Ring   2 Rib Outer Ring   Cage on Outer Ring ID
Long Description	100MM Bore; Straight Bore Profile; 150MM Outside Diameter; 24MM Width; Brass Cage Material; RBEC 1
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer Item Number	NU1020G1C3

Weight / LBS	3.065
Bore	3.937 Inch   100 Millimeter
Outside Diameter	5.906 Inch   150 Millimeter
Width	0.945 Inch   24 Millimeter
bore diameter:	100 mm
static load capacity:	126000 N
outside diameter:	150 mm
precision rating:	ISO Class 0
overall width:	24 mm
maximum rpm:	5400 rpm
flanges:	(2) Outer Ring
bearing material:	Hardened Alloy Steel
bore type:	Straight
cage material:	High Strength Machined Brass Rivetless w/ square holes
number of rows:	1
finish/coating:	Uncoated
internal clearance:	C3
closure type:	Open
ring separation:	Separable Inner Ring
fillet radius:	1.5 mm
operating temperature range:	-40 to 120 °C
manufacturer product page:	<a href="#">Click here</a>
dynamic load capacity:	93000 N