

# CYSD NU1004 cylindrical roller bearings

CYSD NU1004 cylindrical roller bearings Engineering Calculator , 140 mm da Manufacturing Service . Get Your Free.

da	140 mm
db	158.75 mm
dc	134.938 mm
Da	250 mm
Ca	77.8 mm
A1	149.225 mm
A2	260.35 mm
S	4.763 mm
ba	61.119 mm
H	298.45 mm
H1	152.4 mm
H2	60.325 mm
J min.	406.4 mm
J max.	434.975 mm
J1	85.725 mm
L	511.175 mm
N1	28.575 mm
R1	87.313 mm
R2	38.1 mm
RG	3/4 NPT
PG	1/4 NPT
h	51.594 mm
Housing	SAFS 228

Bearing	22228 CC/W33
Lock nut	AN 28
Lock washer	W 28
Stabilizing ring	SR-28-0
Taconite seal (db shaft position)	TER 144
Taconite seal (dc shaft position)	TER 127
End plug (suffix Y)	EPR 16
Max. speed for Taconite seal	490 r/min
P60°	301 kN
P90°	180 kN
P120°	116 kN
P150°	105 kN
P180°	127 kN
Pa	82.3 kN
Mass pillow block	85.3 kg
Cap bolt	7/8-9 UNC
Cap bolt recommended tightening torque	813.5 N·m
Cap bolt, SAE grade	8
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	1 in
Initial grease fill	481.95 g