

EST206 SNR A 37 mm Bearing units

| | |
|---|---------|
| A2 | 28 mm |
| B | 23.8 mm |
| A5 | 14.8 mm |
| d1 | 44.1 mm |
| G | M6x1 |
| H2 | 56 mm |
| N2 | 37 mm |
| s1 | 27.8 mm |
| S | 9 mm |
| SW | 4 mm |
| C | 19.5 kN |
| C0 | 11.2 kN |
| T min. | -20 °C |
| T max. | 100 °C |
| Recommended tightening torque for set screw | 11.5 Nm |
| Designation of housing | T206- |
| Designation of bearing | ES206G2 |
| Bearing number | EST206 |
| Brand | SNR |
| Bore Diameter (mm) | 30 |
| d | 30 mm |
| L4 | 57 mm |
| L5 | 16 mm |
| L2 | 10 mm |
| L3 | 70 mm |

| | |
|-------------------------------|---------|
| s | 9 mm |
| A | 37 mm |
| A1 | 28 mm |
| B1 | 35.7 mm |
| D2 | 44.5 mm |
| H | 102 mm |
| H1 | 56 mm |
| L | 113 mm |
| L1 | 41.5 mm |
| N | 22 mm |
| N1 | 37 mm |
| Thread (G) | M6x1 |
| J1 | 12 mm |
| J2 | 89 mm |
| Weight | 1.2 Kg |
| Basic dynamic load rating (C) | 19.5 kN |