

# Excavator Case Cx36b, Cx31b, Kobelco 35sr-3, 35sr-5 Slewing Ring, Swing Circle P/N: Pw40f00004f1

Excavator Case Cx36b, Cx31b, Kobelco 35sr-3, 35sr-5 Slewing Ring, Swing Circle P/N: Pw40f00004f1, Units and 0.0 Inventory Housings CAD models , N/A Minimum Buy Quantity TIMKEN Manufacturer Name Manufacturing Service . Get Your Free.

Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	1.587 lb
EAN	0087796057845
Product Group	M06110
Number of Mounting Holes	2
Mounting Method	Set Screw
Housing Style	2 Bolt Flange Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	11.5 Millimeter
Relubricatable	Yes
Insert Part Number	GYAE30RRB
Seals	Double Land Riding Rubber Contact
Housing Configuration	1 Piece Solid

Pilot Configuration	No Pilot
Inch – Metric	Metric
Long Description	2 Bolt Flange Block; 30MM Bore; 117MM Bolt Circle; 116.7MM Bolt Spacing; 1 Piece Solid; Set Screw Mo
Other Features	Single Row   Normal Duty   Narrow Inner Race
UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Flanged
Manufacturer Item Number	SCJT 30
Weight / LBS	1.58
Cartridge Pilot Diameter	0 Inch   0 Millimeter
Cartridge Pilot Depth	0 Inch   0 Millimeter
Nominal Bolt Circle Diameter Round	4.6 Inch   117 Millimeter
Bolt Spacing	4.594 Inch   116.7 Millimeter
d	1.181 Inch   30 Millimeter
D	1.28 Inch   32.5 Millimeter
Shaft Size d	1.181 in
Bearing Type	Ball Bearing
Dimension E	1.343 in
Inside Ring Outside Diameter	1.579 in
Series	Standard
Seal Type	Narrow Shroud
Total Length H	141.3 mm
Total Height L	79.4 mm

Housing Width A	0.843 in
Bolt Hole Spacing J	116.68 mm
Bolt Hole Size N	11.5 mm
Flange Thickness A1	13.5 mm
Center of Bearing from Housing End A2	11.1 mm
Inside Ring Width B	32.5 mm
Center of Bearing from Bearing End S	11.1 mm
Static Load Rating	2530 lbf
Dynamic Load Rating	4850 lbf