

# Excavator Caterpillar Cat320L Swing Circle, Slewing Bearing, Slewing Ring

What are the types of Excavator Caterpillar Cat320L Swing Circle, Slewing Bearing, Slewing Ring ? 1060 Bore Diameter (mm) Manufacturing 1060x800x258 Size (mm) Service . Get Your Free, Instant price, 800 Outer Diameter (mm) design review.

Size (mm)	1060x800x258
Bore Diameter (mm)	1060
Outer Diameter (mm)	800
Width (mm)	258
d	800 mm
D	1060 mm
B	258 mm
d2	887 mm
D1	973 mm
b	22.3 mm
K	12 mm
r1,2 – min.	6 mm
da – min.	823 mm
Da – max.	1037 mm
ra – max.	5 mm
Basic dynamic load rating – C	8136 kN
Basic static load rating – C0	19300 kN
Fatigue load limit – Pu	1060 kN
Reference speed	240 r/min
Limiting speed	430 r/min

Calculation factor – e	0.21
Calculation factor – Y1	3.2
Calculation factor – Y2	4.8
Calculation factor – Y0	3.2
d2 ≈	887 mm
D1 ≈	973 mm
r1,2 min.	6 mm
da min.	823 mm
Da max.	1037 mm
ra max.	5 mm
Basic dynamic load rating C	8136 kN
Basic static load rating C0	19300 kN
Fatigue load limit Pu	1060 kN
Calculation factor e	0.21
Calculation factor Y1	3.2
Calculation factor Y2	4.8
Calculation factor Y0	3.2
Mass bearing	640 kg