

Excavator Hyundai R210LC-7A Slewing Bearing, Slewing Ring, Swing Circle

We Provide 60x95x23 Size (mm) 95 Outer Diameter (mm) Extensive Excavator Hyundai R210LC-7A Slewing Bearing, Slewing Ring, Swing Circle Selection And Competitive Wholesale Pricing. 60 Bore Diameter (mm)

Size (mm)	60x95x23
Bore Diameter (mm)	60
Outer Diameter (mm)	95
Width (mm)	23
d	60 mm
D	95 mm
T	23 mm
α	3 °
dk	88.5 mm
B	23 mm
C	21 mm
r1 – min.	1.5 mm
r2 – min.	0.6 mm
s	5.7 mm
da – max.	68 mm
db – max.	77 mm
Da – min.	70 mm
Db – min.	90 mm
ra – max.	1.5 mm

Basic dynamic load rating – C	69.5 kN
Basic static load rating – C0	112 kN
Specific factor dynamic load – K	50 N/mm ²
Specific factor static load – K0	80 N/mm ²
Constant – KM	480
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.73
EAN	7316577003065
Product Group	B04264
Rolling Element	Spherical Plain
Self Aligning	Yes
Material – Outer Member	Steel
Material – Ball	Steel
Material – Liner	Plastic Teflon
Enclosure	Open
Relubricatable	No
Other Features	Angular Contact Single Direction Axially Split Self Lubricating Maintenance Free
Long Description	60MM Bore; 95MM Housing Outside Diameter; 23MM Overall Width; Spherical Plain; Self Aligning; Steel
Inch – Metric	Metric

UNSPSC	31171515
Harmonized Tariff Code	8483.30.80.70
Noun	Bearing
Keyword 3	Spherical
Keyword String	Plain Thrust Spherical
Manufacturer Item Number	GAC 60 F
Weight / LBS	1.609
Overall Width	0.906 Inch 23 Millimeter
Housing Width	0.827 Inch 21 Millimeter
Bore	2.362 Inch 60 Millimeter
Housing Outside Diameter	3.74 Inch 95 Millimeter
Ball Outside Diameter	3.484 Inch 88.5 Millimeter
bore diameter:	60 mm
outer ring width:	21 mm
outside diameter:	95 mm
race material:	PTFE Composite
misalignment angle:	3 °
overall width:	23 mm
inner ring width:	23 mm
radial static load capacity:	112 kN
bearing type:	Angular Contact
radial dynamic load capacity:	69.5 kN
lubrication type:	Maintenance Free/Self-Lubricating
operating temperature range:	-40 to + 165 °F °F
closure type:	Open
weight:	1.61 lbs
outer ring material:	Steel

manufacturer product page:	Click here
inner ring material:	Steel
manufacturer upc number:	7316577003065
α	1.7 °
r1 min.	1.5 mm
r2 min.	0.6 mm
da max.	68 mm
db max.	77 mm
Da min.	70 mm
Db min.	90 mm
ra max.	1.5 mm
Basic dynamic load rating C	78 kN
Basic static load rating C0	125 kN
Specific dynamic load factor K	50 N/mm ²
Specific static load factor K0	80 N/mm ²
Material constant KM	480
Mass plain bearing	0.73 kg