

# Excavator Komatsu PC228us3 Slewing Ring, Swing Circle, Slewing Bearing

The online Excavator Komatsu PC228us3 Slewing Ring, Swing Circle, Slewing Bearing parts store gives 95x200x45 Size (mm) you immediate access to a selection of more than 1.4 million new, used, remanufactured.

Size (mm)	95x200x45
Bore Diameter (mm)	95
Outer Diameter (mm)	200
Width (mm)	45
d	95 mm
D	200 mm
B	45 mm
C	45 mm
Angle ( $\alpha$ )	30 °
a	20.1 mm
r min.	3 mm
r1 min.	1.1 mm
da min.	109 mm
Da max.	186 mm
ra max.	2.5 mm
Weight	6.68 Kg
Basic dynamic load rating (C)	183 kN
Basic static load rating (C0)	163 kN
(Grease) Lubrication Speed	3000 r/min
Configuration	Single Row

Enclosure	Open
Bore Type	Cylindrical Bore
Bore Size	95 mm
Outside Diameter	200 mm
Width	45 mm
Fillet Radius/Chamfer	3 mm
r1	1.1 mm
Dynamic Load Rating	183,000 N
Static Load Rating	163,000 N
Limiting Speed – Grease	3,000 rpm
Limiting Speed – Oil	4,000 rpm
da1 (min)	109 mm
da2 (min)	102 mm
Da1 (max)	186 mm
Da2 (max)	193 mm
ra (max)	2.5 mm
ra1 (max)	1 mm